



80 Cypress Street, Warwick, RI 02888 ♦ U.S.A.
401-941-3000 ♦ 800-272-7752 ♦ Fax: 1-401-941-0150
info@rbcepoxy.com ♦ www.rbcepoxy.com

♦ TECHNICAL BULLETIN ♦ TECHNICAL BULLETIN ♦ TECHNICAL BULLETIN ♦

Ultra Violet Curable Resin # 2019 LVT

DESCRIPTION:

UV 2019 LVT is a clear polyurethane protective finish for plastics, wood and some metals. UV 2019 LVT is low in viscosity, and may be sprayed as received without the use of solvents. UV 2019 LVT provides a durable, high gloss wet look.

APPLICATIONS:

- Protective coating for most plastics and wood, providing a durable, scratch resistant finish.
- Top coat for wood to provide scratch and moisture resistance.
- Conformal coating for PC boards and electronic components.

BENEFITS:

- Cures in seconds to increase productivity.
- Process flexibility.
- One component, thus no waste, no mixing, no pot life.
- Sprayable with conventional equipment.

LIQUID CHARACTERISTICS:

Resin..... Polyurethane
Color..... Clear
Viscosity..... 600 cps
Specific Gravity..... 1.1

CURE CHARACTERISTICS:

5 seconds @ 2 mil
300 watts/in. intensity.

SPECIFICATIONS:

All technical information and data on this sheet are for comparison purposes only. Actual values may differ due to circumstances beyond our control. Keep product tightly sealed and away from light. Keep away from skin.

The manufacturer, RBC Industries, Inc., hereby gives notice that any statement or representation made by the manufacturer in the sales of any and all of its products shall not create any warranty of merchantability expressed or implied. Statements or descriptions are informational only and the purchaser shall be solely responsible for determining the adequacy of the product for any and all uses.